




Work Smarter with Honeywell Switches and Sensors

Due to the high cost of energy, HVAC systems need to be efficient, accurate, and reliable. Honeywell's broad line of sensors and switches covers HVAC control, monitoring, temperature, and more while maintaining energy efficiency and accuracy. Honeywell Sensing and Productivity Solutions provides industry-leading products with the latest technology that are easy to install and maintain while delivering precise, dependable performance.

Air Filter, Cooling Coil, and Fan/Blower



Damper




Refrigerant Monitoring and Control




Boiler



Duct Work, VAV, and Remote Transmitter



Chiller




Power and Temperature Monitoring and Management



Cooling Tower




Pump



- Measures differential pressure**
- A Board Mount Pressure Sensors:** TruStability® HSC and SSC Series; Basic ABP Series
- Monitors pressure to prevent a potentially explosive situation**
- B Pressure Switches:** HP, HE, ME, LP, LE Series
- Maintains occupant comfort for desired humidity and temperature levels**
- C Humidity Sensors:** Honeywell HumidCon™: HIH6000, HIH6100, HIH7000, HIH8000, HIH9000
- Monitors system performance for proper environmental control**
- D Heavy Duty Pressure Sensors/Transducers:** PX Series, MLH Series, 13 mm/19 mm Series
- Monitors temperature**
- E Temperature Probes:** R300 Series, 6655 Series, 500 Series
- Provides high-performance mechanical switching**
- MICRO SWITCH™ Large Premium Basic Switches:** BZ, WA Series; DT Series
- F MICRO SWITCH™ V-Basic Switches:** V7 Series, V15 Series
- MICRO SWITCH™ Miniature and Subminiature Switches:** SM Series; SX Series; ZM, ZW, ZX Series
- Helps brushless dc motors run smoothly, quietly, and efficiently**
- G Hall-effect/MR Sensor ICs:** SS361RT/SS461R, SS30AT/SS40A, SS40F/SS40G, SS42R, APS00B, SS490; Nanopower Series: SM351LT/SM353LT; Standard Power Series: SM351RT, SM451R, SM353RT, SM453R
- H Measures and monitors airflow**
- Airflow Sensors:** HAF Series, AWM1000 Series
- Provides energy management, amp draw status, and kilowatt consumption**
- I Current Sensors:** CSNX25 Series
- Controls power and other functions near flammable hydrocarbon refrigerants**
- J MICRO SWITCH™ Toggle Switch:** NT Series
- Provides temperature control or over-temperature protection**
- K Commercial Thermostats:** 2450, 2455 Series

Sensors and Switches for Potential Use in HVAC Applications

Pressure Sensors and Transducers



Board Mount Pressure Sensors, Basic, ABP Series

- Cost effective, energy efficient, calibrated, and temperature compensated
- As small as 8 mm x 7 mm
- Industry-leading long-term stability: $\pm 0.25\%$
- Industry-leading accuracy: $\pm 0.25\%$ FSS BFSL
- Total Error Band: $\pm 1.5\%$
- Pressure range: 60 mbar to 10 bar; 6 kPa to 1 MPa; 1 to 150 psi
- Wide variety of pressure ranges and package styles available



Board Mount Ultra-Low Pressure Sensors, TruStability® HSC and SSC Series

- Industry-leading long-term stability
- Extremely tight accuracy of $\pm 0.25\%$ FSS BFSL
- Total Error Band of $\pm 1\%$ (HSC) or $\pm 2\%$ (SSC) full scale span max
- Pressure ranges from ± 2.5 mbar to ± 40 mbar [± 1 in H_2O to ± 30 in H_2O]
- Low operating voltage and extremely low power consumption
- Wide variety of pressure ranges and package styles available



Heavy Duty Pressure Transducers, PX3 and PX2 Series

- Designed for configurability - multiple ports, connectors, pressure ranges
- Pressure range: 1 to 46 bar | 15 to 667 psi (PX3 Series); 1 to 70 bar | 100 kPa to 7 MPa | 15 to 1000 psi (PX2 Series)
- 1 %FSS typ. Total Error Band accuracy (PX3 Series); 2 %FSS typ. TEB (PX2 Series)
- Compatible with common HFC refrigerants and low GWP refrigerants such as R32 and R1234ZE, petroleum oils, lubricants, hydraulic/brake fluids, air, water
- Rated IP65 or better for protection in harsh environments



Heavy Duty Pressure Transducers, MLH Series


- All-metal wetted parts for use in wide variety of fluid applications
- Compatible with ammonia, common HFC refrigerants, and many low GWP next generation refrigerants such as R32 and R1234ZE
- Range: 50 psi to 8000 psi (inclusive)
- Voltage and 4 mA to 20 mA current output options
- Rated IP65 or better for protection against harsh environments



Heavy Duty Pressure Sensors, 13 mm/19 mm Series


- Stainless 316L wetted materials for enhanced corrosion resistance
- Pressure ranges up to 5000 psi (inclusive)
- Millivolt output option; compact size
- Low power consumption; compensated or uncompensated

Hall-Effect/Magnetoresistive Sensor ICs




Bipolar Hall-Effect Position Sensor ICs, SS30AT/SS40A

- Sensitive bipolar magnetics respond to alternating North and South poles
- Miniature (SS40A) and subminiature (SS30AT) sizes fit small spaces
- Durable design with built-in reverse voltage protection for simplified installation and device damage protection
- Thermally balanced integrated circuit for stable operation over full temperature range of -40 to $125\text{ }^\circ\text{C}$ [-40 to $257\text{ }^\circ\text{F}$]




Bipolar Latching Hall-Effect Digital Sensor ICs, SS361RT/SS461R

- Small, versatile digital Hall-effect devices operated by magnetic field from a permanent magnet or an electromagnet
- Enhanced sensitivity often allowing use of less expensive magnets
- Miniature package size, built-in reverse voltage protection
- Low voltage: 3 V operation - promotes energy efficiency
- Robust design: operates up to $150\text{ }^\circ\text{C}$ [$302\text{ }^\circ\text{F}$]




Bipolar, Low-Cost Hall-Effect Sensor ICs, SS40F/SS40G

- Miniature construction in plastic package
- Low power consumption (5 mA max at 4.5 Vdc) for energy efficiency
- Bipolar magnetic for ring magnet applications
- High speed operation range: 0 kHz to over 100 kHz
- Broad temperature range: $-40\text{ }^\circ\text{C}$ to $125\text{ }^\circ\text{C}$ [$-40\text{ }^\circ\text{F}$ to $257\text{ }^\circ\text{F}$]



Bipolar Hall-Effect Digital Sensor ICs, SS42R

- Digital dual complementary sink / source outputs
- Reverse voltage polarity protection for full supply range
- Operate release points are trimmed for zero symmetry
- High output current capability
- Small 4-pin SIP package




Linear Hall-Effect Sensor ICs, SS490

- Small size with low power consumption
- Single current sinking or current sourcing linear output
- Built-in thin-film resistors are laser trimmed for precise sensitivity and temperature compensation
- Rail-to-rail operation provides more usable signal for higher accuracy
- Responds to either positive or negative gauss
- Quad Hall sensing element for stable output



Magnetoresistive Sensor ICs, Nanopower Series (SM351LT/SM353LT); Standard Power Series (SM351RT/SM451R/SM353RT/SM453R)


- Package size: SOT-23 (SM351LT/SM353LT/SM351RT/SM353RT); flat TO-92 (SM451R/SM453R)
- Sensitivity: 7 G typ., 11 G max. (SM351LT/SM351RT/SM451R); 14 G typ., 20 G max. (SM353LT/SM353RT/SM453R)
- Supply voltage: 360 nA typ. (SM351LT), 310 nA typ. (SM353LT), 3 Vdc to 24 Vdc (SM351RT/SM451R/SM353RT/SM453R)
- Omnipolar sensing activates with either pole from a magnet
- Temperature range: $-40\text{ }^\circ\text{C}$ to $85\text{ }^\circ\text{C}$ [$-40\text{ }^\circ\text{F}$ to $185\text{ }^\circ\text{F}$]
- Push-pull output: Does not require external pull-up resistor (SM351LT/SM353LT)
- Non-chopper stabilized design (SM351LT/SM353LT)



Magnetoresistive High-Res Magnetic Displacement Sensor ICs, APS00B

- Cost-effective, space-efficient solution for high volume OEM designs
- Wide, angular range allows measurements of $\pm 90^\circ$ without additional components
- Measures only field direction; virtually unaffected by shock, vibration, magnetic-source gap variations
- Low power consumption (5 V at 4 mA Vdc) for energy efficiency
- Tape and reel packaging

Humidity/Temperature Sensors



Digital Humidity/Temperature Sensors, Honeywell HumidCon™ HIH6000, HIH6100, HIH7000, HIH8000, HIH9000 Series

- Combined digital output-type relative humidity (RH) and temperature sensor
- Industry-leading long term stability (1.2% RH over five years)
- Industry-leading reliability (MTTF 9,312,507 HR)
- Industry-leading relative humidity accuracy
- Lowest total cost solution; true, temperature-compensated digital I²C and SPI output
- Energy efficient; ultra-small package

Temperature Sensors and Probes



Immersion Temperature Probes, R300 Series

- One-piece passive, resistive temperature device (RTD), high temperature probe
- Excellent reliability, response time, and accuracy
- Working temperature range: $-40\text{ }^\circ\text{C}$ to $275\text{ }^\circ\text{C}$ [$-40\text{ }^\circ\text{F}$ to $527\text{ }^\circ\text{F}$], continuous
- Durable stainless steel closed tip design



Surface Temperature Probes, 500 Series

- Broad portfolio of air/gas, liquid, and surface temperature probes
- Small, easy-to-install assemblies
- Enhanced reliability, precision, sensitivity, and stability for greater flexibility
- Operating temperature range: $-60\text{ }^\circ\text{C}$ to $300\text{ }^\circ\text{C}$ [$-76\text{ }^\circ\text{F}$ to $572\text{ }^\circ\text{F}$]
- Wide variety of housing styles and materials; custom options available



On Surface Temperature Sensors, 6655 Series


- Thermistor-based NTC temperature sensors
- For use in surface/pipe temperature applications in non-condensing environments
- Wide operating temperature range: $-20\text{ }^\circ\text{C}$ to $110\text{ }^\circ\text{C}$ [$-4\text{ }^\circ\text{F}$ to $230\text{ }^\circ\text{F}$]
- Extended life and stable output; enhanced accuracy and response time
- Small size; variety of packages, R-T curves, termination styles, and housing materials



Commercial Thermostats, 2450 Series, 2455 Series

- Affordable, robust, customizable
- Small size with no programming required
- Operating temperature range: $0\text{ }^\circ\text{C}$ to $260\text{ }^\circ\text{C}$ [$32\text{ }^\circ\text{F}$ to $500\text{ }^\circ\text{F}$]

Current Sensors



Closed Loop Current Sensors, CSNX25 Series

- Current sensing up to 1275 A (depending on product listing)
- Measures ac, dc, and impulse currents
- Competitive cost/performance ratio
- Rapid response and high overload capability
- Industrial operating temperature range, small size, and weight

Airflow Sensors



Honeywell Zephyr™ High Accuracy Airflow Sensors, HAF Series

- Small size with low power consumption
- Single current-sinking or current-sourcing linear output
- Built-in thin-film resistors; laser trimmed for precise sensitivity & temperature comp.
- Rail-to-rail operation provides more usable signal for higher accuracy
- Responds to either positive or negative gauss
- Quad Hall sensing element for stable output



Signal Conditioning Airflow Sensors, AWM1000 Series


- Accurate, repeatable airflow sensing
- Cost-effective, micro-bridge technology
- Bi-directional sensing capability
- Low differential pressure sensing

MICRO SWITCH™ Basic Switches




MICRO SWITCH™ Premium Large Basic Switches, BZ and WA Series; DT Series

- Accepted world-wide standard "Large Basic" switch
- Low operating force and differential travel
- Long mechanical life up to 20,000,000 cycles at 95 % survival
- Elongated mounting hole for easier, more accurate mounting
- Current rating ranges from 15 A to 25 A
- Choice of actuation, termination and operating characteristics
- Two independent single-pole double throw circuits in one housing and actuator (DT)



MICRO SWITCH™ Premium V-Basic Switches, V7 Series

- Best suited for higher cost-of-failure applications
- Designed for 100K operations at full load or 10M for mechanical life
- World-wide package size acceptance
- Current rating ranges from 0.1 A to 25 A
- UL/CSA and ENEC approvals




MICRO SWITCH™ Standard V-Basic Switches, V15 Series

- Best suited for lower cost-of-failure applications
- Designed for 10K to 50K operations at a full load or 5M for mechanical life
- World-wide package size acceptance
- Current rating ranges of 10 A and 26 A
- UL/CSA, cUL, ENEC, and CQC approvals



MICRO SWITCH™ Premium Miniature/Subminiature Switches, SM/SX Series

- Best suited for high cost-of-failure applications
- Small, lightweight; extended operating life
- Elongated mounting hole for easy, accurate mounting
- Choice of actuation, electrical termination, and gold contact options for low energy switching and reliability
- UL/CSA, CE, ENEC approvals



MICRO SWITCH™ Standard Miniature/Subminiature Switches, ZM/ZW/ZX Series

- Best suited for lower cost-of-failure applications
- Small, lightweight, low cost, enhanced life, ample electrical capability
- Choice of low energy or power-duty electrical ratings (gold plated or silver contacts)
- Choice of ratings, actuation, termination and operating characteristics
- UL/CSA, cUL, ENEC, and CE approvals

Toggle Switches



MICRO SWITCH™ Toggle Switches, NT Series

- ISA 12.12.01 certified; designed for use near flammable hydrocarbon refrigerants
- Quick-connect spade terminals
- UL191 electrical rating
- Sealed to NEMA 3, 3R, 4, 13, and IP67
- Operating temperature range: $-40\text{ }^\circ\text{C}$ to $71\text{ }^\circ\text{C}$ [$-40\text{ }^\circ\text{F}$ to $160\text{ }^\circ\text{F}$]

Pressure Switches



Premium and Economy Pressure Switches, HP/HE/ME/LP/LE Series

- High, medium, and low pressure switches
- Life cycle rating: up to 2 million; IP67 sealing rating
- Set point factory set or field adjustable 3.5 psi to 4500 psi [0.24 bar to 310.26 bar]
- High burst pressure up to 20000 psi [1379 bar]
- Variety of pressure ports, electrical terminations, and compatibility with many media

Find out more

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office. To learn more about Honeywell's sensing and switching products, call +1-815-235-6847/1-800-537-6945, visit sensing.honeywell.com, or e-mail inquiries to info.sc@honeywell.com

Honeywell Sensing and Productivity Solutions

9680 Old Bailes Road
Fort Mill, SC 29707
honeywell.com

000815-2-EN IL50 GLO
April 2016
© 2016 Honeywell International Inc. All rights reserved.

Honeywell