

Duratherm Receipt



- Duratherm Receipt is simple to use and does not require the use of a ribbon.
- Duratherm Receipt products are coated with a heat-sensitive layer which is imaged through direct contact with the Printhead. The result is a pattern of black dots forming text, bar codes, or graphics.
- Available products range from an economical low-caliper paper receipt to a high-performance film receipt with enhanced durability.

Intermec's Duratherm Receipt portfolio represents a range of products that match performance to specific application needs, providing the right product for the job every time.

Duratherm receipt products offer high-quality, cost-effective printing with several levels of durability from uncoated paper receipts to top-coated film receipts. Without the need for ribbon changeover, Duratherm products require less operator intervention and training.

Better Together

The Intermec media solution has added advantages when paired with Intermec printers:

- Co-engineered printers and media ensure consistent print quality and performance
- Thermal transfer printability allows on-demand generation of durable labels, eliminating high cost and inventory obsolescence associated with preprinting

Duratherm Receipt Portfolio

Product	Description	Image Life*	Recommended Applications	Recommended Heat Setting
Duratherm II Receipt	A 2.5-mil non-top-coated paper receipt that provides excellent print quality.	10 Years	Well suited for most general receipt applications, such as retail, coupon, Point Of Sale (POS), and light-weight ticketing.	IPL: 101 Const/Factor: 30/40
Duratherm III Receipt	A 3-mil top-coated paper receipt that delivers high quality printing an enhanced durability.	20 Years	Duratherm III receipt is recommended for applications where high humidity, moisture contact, and surface abrasion are a concern.	IPL: 401 Const/Factor: 45/40
Duratherm S Receipt	A three-mil synthetic polyolefin receipt that provides excellent print quality and enhanced durability as compared to paper products.	15 Years	Duratherm S Receipt is recommended for use in wet environments where chemical contact is not a concern.	IPL: 430 Const/Factor: 80/40

*Image life is based upon the proper storage of the printed receipt in a light-free environment, protected from chemical exposure at 70°F/50%RH.

 **YourLogoHere**

Company Name
123 Your Street
City, State Zip
123.456.7890
info@YourURL.com
www.YourURL.com

 **Intermec**
PartnerNet

Copyright © 2011 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 612116-02A 03/11

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.